


ez Effort® Lift

Features and Specifications – 750 lb. Capacity

"Your Partner In Safe Patient Handling"



▶ Frame:

- · All steel construction
- Power leg spreading
- Clearance with standard casters 4.5"
- Baked epoxy powder coated paint
- Weight with battery pack 145 pounds
- Lift range 27" 76" total travel

► Covers and Bumpers:

ABS plastic covers on base and foot of leg

Casters:

- Front: Two 4" double rubber tread swivel
- Rear: Locking, 4" double rubber tread swivel

► Hand Control:

• Impact resistant, IPX 6 rated, encased magnet, built-in LCD display

► Motor Actuator:

- Acme screw design
- Built in safety switch for down stroke
- Automatically stops at top and bottom of stroke
- CE certified
- Manual lowering capability if there is a power failure

► Battery Pack: (2 per Lift)

- Lithium Ion
- 1-125.7V, 2.9 AMP/HR
- Approximately 100 lifts per charge

► Battery Charger Unit:

- 110 volt input/24 volt output
- Approved to UL Standards
- 4 hour charge

Electronics:

- Three methods to control the unit, hand control, buttons on the Secondary Control Box, raise and lower boom from control box
- Built-in LCD displays in hand control shows battery level, patient weight (if equipped), and diagnostic functions
- · Automatically shuts off after non-use
- Leg spreading
- Over-discharge protection
- Usage time captured: Lift usage time is captured in minutes, great for tracking frequency of use
- Overload protection
- Displays weight in pounds or kilograms