



EZ Way, Inc.

*"Your Partner in
Safe Patient Handling"*

eZ EFFORT® LIFT

Mobile full-body floor lift with 500, 750, & 1,000 lb. weight capacities.



Safe, efficient, and reliable lifting for even your most complex mobility needs.

DURABLE CONSTRUCTION

- All-steel frame with baked epoxy powder-coated paint for long-lasting performance

ADVANCED ELECTRONICS

- Three control methods (hand control, secondary control panel, control box)
- Automatic shut-off after inactivity
- Over-discharge and overload protection
- Tracks lift usage time (ideal for care auditing and ROI analysis)

LCD HAND CONTROL WITH BUILT-IN DISPLAY

- Water-resistant, impact-rated display shows battery life, patient weight (if equipped), functions, and diagnostics.

EZ EFFORT LIFT APPLICATIONS:

- Lifting and transferring persons from beds, wheelchairs, commodes, or the floor
- Weighing during transfer (integrated scale models)
- Repositioning, turning, or elevating limbs for woundcare and therapy
- Safe therapy and early mobility training



Low Profile Base

Optional low base for use with low clearance beds and stretchers.



Floor Lifting

Ability to lift people from the floor.

"Your Partner in Safe Patient Handling"



Model EL500:

EL500N - 500 lb.
EL500S - 500 lb. w/scale
ELL500N - 500 lb. Low Profile Leg
ELL500S - 500 lb. Low Profile Leg w/scale



Model EL750:

EL750N - 750 lb.
EL750S - 750 lb. w/scale



Model EL1000:

EL1000N - 1000 lb.
EL1000S - 1000 lb. w/scale

ADDITIONAL FEATURES:

- 10 Year frame / 3 year component warranty
- Power leg spreading (500 lb. & 750 lb. models). Three-position base opening (1,000 lb.)
- Lithium-ion battery powered
- Digital scale available
- Low-base, 2", 4" and 5" casters available for low clearance of special beds or ease of function on carpeted flooring
- Emergency stop safety control
- Emergency lowering option
- Anti-crush feature
- 24-Hour service hotline with remote log-in access
- Includes 2 batteries and remote charger.

	500 lb. Unit	750 lb. Unit	1000 lb. Unit
Battery Power	2 - Lithium-ion		
Remote Charging Unit	1 - 110V UL listed. 4 hour charge.		
Base Dimensions w/ 4" Standard Caster	28.5" w x 49.5" l x 4.5" h	29" w x 60.675" l x 4.5" h	34" w x 62" l x 4.5" h
Base Height w/ 2" Caster	3.25"		
Base Height w/Low Base	2.25"		N/A
Sling Bag	Optional		
Digital Scale	Optional		

EZ EFFORT LIFTS HAVE A 10 YEAR LIFE CYCLE



Visit Our Website For More
Information And Resources



Proud to Be a US Manufacturer
of Safe Patient Handling Products

PO Box 89, 807 E. Main • Clarinda, IA 51632 • 1-800-627-8940

Form #2-417
Rev. 08/28/2025

⚠️WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.