






EZ Way, Inc.

*"Your Partner In
Safe Patient Handling"*

eZ Effort® Lift

Features and Specifications – 1,000 lb. Capacity



► Frame:

- All steel construction
- Three position leg spreader (hand operated)
- Clearance with standard casters 4.5"
- Baked epoxy powder coated paint
- Weight with battery pack – 216 pounds
- Lift range 30.5" - 83.5"

► Covers and Bumpers:

- ABS Plastic covers on base and legs

► Casters:

- Front: Two, 4" double rubber tread swivel
- Rear: Locking, 4" double rubber tread swivel

► Hand Control:

- Impact resistant, IPX 6 rated, electric, encased magnet

► Motor Actuator:

- Acme screw design
- Built in safety switch for down stroke
- Automatically stops at top and bottom of stroke
- CE certified
- Manual lowering capability if there is a power failure

► Battery Pack: (2 per Lift)

- LithiumIon
- 1-25.7V, 2.9AMP/HR
- Approximately 100 lifts per charge

► Battery Charger Unit:

- 110 volt input/24 volt output
- Approved to UL Standards
- 4 hour charge

► Electronics:

- Three methods to control the unit, hand control, buttons on the Secondary Control Box, raise and lower boom from control box
- Built-in LCD displays in hand control shows battery level, weight (if equipped), and diagnostic functions
- Automatically shuts off after non-use
- Leg spreading
- Over-discharge protection
- Usage time captured: Lift usage time is captured in minutes, great for tracking frequency of use
- Overload protection
- Displays weight in pounds or kilograms (scale models)