

The EZ Way load testing sling is designed to safely and effectively perform the load testing step of the recommended preventative maintenance schedule. It is designed to be used in conjunction with common bagged materials (such as bags of sand or bags of Portland cement mix) that are placed in the load testing sling to come near to the rated weight capacity of the EZ Way lift.

Steps to using and conducting a load test with the EZ Way Load Testing Sling:

1. With the lift legs spread, place the load testing sling in between the legs of the lift with a narrow side of the sling facing the lift mast.
2. Turn the lift hanger assembly so that the sling hanger bars are parallel with the lift boom.
3. Attach each loop of the load testing sling to the nearest hanger bar hook. (Fig A)
4. Raise the lift boom up so that the load testing sling rests lightly upon the floor. Push open the sides of the load testing sling to give ample room to place bags into the sling.
5. Place the common bagged materials into the sling to reach or come near the rated weight capacity of the lift. (Fig B)
6. Raise the lift boom using the hand control (Smart Lift and Classic Lift), toggle (Smart Lift), or user interface (Smart Lift) until you feel tension on the loops. (FIG C) Pause and check that all four loops are secure on the hanger bar hooks and then raise and lower the load with the lift. Listen for any unusual noises while operating the unit. With the test load applied to the lift, check all structural welds for any signs of stress or fatigue cracks. If any unusual noises or cracks are found, stop using the lift and call the EZ Way Service Department immediately!



(Fig A)



(Fig B)



(Fig C)